



NOTES: (UNLESS OTHERWISE SPECIFIED)

- EXCEPT AS NOTED, DIMENSIONS ARE IN MILLIMETERS.
- THICKNESS MAY VARY AS REQUIRED BY FIELD FIT.
- COAT WITH AISC CLASS A COATING FOR SLIP-CRITICAL CONNECTIONS.

D	PO	PF-350-620-21		1					
		REV	DESCRIPTION			DRN	CHK	APP	DAT

1	-	-	-	PLT,STL, 300mmX250mmX30mm	1
ITEM NO	PREF	BAS	SUFF	TITLE OR DESCRIPTION	QTY
	STOCK OR PART NO				

	DIMENSIONING AND TOLERANCING IS IN ACCORDANCE WITH ANSI Y14.5M-1982.		SCALE 1 : 2		DO NOT SCALE DRAWING		CAD FILE NAME: PF35062021.P0	
	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS TOLERANCES BREAK EDGES .005-.015 INTERNAL CORNERS .015 R MAX FRACTIONS + --- DEC .xx + --- .xxx + --- .xxxx + ---		STANFORD LINEAR ACCELERATOR CENTER U.S. DEPARTMENT OF ENERGY STANFORD UNIVERSITY STANFORD, CALIFORNIA PROPRIETARY DATA OF STANFORD UNIVERSITY AND/OR U. S. DEPARTMENT OF ENERGY. RECIPIENT SHALL NOT PUBLISH THE INFORMATION WITHIN UNLESS GRANTED SPECIFIC PERMISSION OF STANFORD UNIVERSITY.				BABAR DETECTOR BARREL FLUX RETURN SHIM PLATE, 4 HOLE	
SA-350-620-00	DEC .xx + --- .xxx + --- .xxxx + ---		ENGR R.F. BOYCE 1/24/96 DRW R.F. BOYCE 1/24/96 CHKD H.J. KREBS 3/21/96		APPROVAL SR A BELL 3/22/96 H.L. LYNCH 3/22/96 T O'CONNOR 3/22/96			
NEXT ASSEMBLIES:	ALL SURFS							

BBR BRRL FLX RTN SHIM PLATE 4